

QUADTRAC & STEIGER

QUADTRAC & STEIGER

TRACTORS FROM
475 – 715 hp



CASE IH

CASE IH

QUADTRAC & STEIGER

GREATER EFFICIENCY

11 models from 475 to 715 hp

With updated styling, built-in precision technology, a brighter lighting package and an enhanced operator environment, the legendary Quadtrac & Steiger series tractors remain the go-to tractor for producers wanting a reliable, efficient and powerful four-wheel drive tractor.

COMFORT AT THE HIGHEST LEVEL

- Intuitive Vision Pro operating system featuring new Case IH PRO 1200 LCD monitor
- New intuitive and ergonomic controls developed with our customers
- Industry-leading configurable buttons can be programmed with over 100 functions
- The new Heavy-Duty Suspension increases operator comfort due to hydraulically suspended, ground conforming undercarriage. Higher field travel speeds in rough conditions

IMPRESSIVE PERFORMANCE

- Powerful engine with up to 778 hp maximum power
- Up to 428 litres per minute flowrate for up to eight hydraulic remote valves
- Colossal rear lift capacity of 10,092 kg

NEVER EQUALLED

- Articulated steering and Tri-Point Oscillation delivers full power
- Four-track design distributes weight evenly over a total footprint of up to 5.91 m²
- Oscillation of 26° is provided both upwards and downwards
- Maximum 170 L/min flow rate at valve

LED

worklights with
76,620 lumens

NEW

Heavy-Duty Suspension

5.91 m²
total footprint HDS
undercarriage



ENHANCED PROTECTION

- 3 Years SAFEGUARD CONNECT* Package includes:
 - 3 years extended warranty
 - Connectivity included
 - 24/7 MAXSERVICE
 - Pre-season check
 - Operator training by the dealer
- CNH Capital professional financing solutions for every investment

CONNECTIVITY MEANS EFFICIENCY

- FieldOps Telematics solution – the gateway to Quadtrac series tractors
- Extended remote capabilities
- Manage and optimize your farm, fleet, and data with FieldOps at any time
- Remote screen sharing

* ask your Dealer for the availability, terms and conditions of Safeguard Connect for your new Case IH machine

Scan for more
information!



Model	Rated power ECE R120 ¹⁾ @ 2,200 rpm [kW/hp (CV)]	Maximum power ECE R120 ¹⁾ [kW/hp (CV)]	Transmission	Max. lift capacity [kg]	Max. pump flow Standard (Option) [l/min]	Track width Standard (Option) [cm]
QUADTRAC 715	527 / 715	572 / 778	16F/2R PowerDrive	10,092	159 (216 or 428)	76 (91)
QUADTRAC 645	474 / 645	514 / 699	16F/2R PowerDrive	10,092	159 (216 or 428)	76 (91)
QUADTRAC 595	438 / 595	482 / 656	16F/2R PowerDrive	10,092	159 (216 or 428)	76 (91)
QUADTRAC 555	408 / 555	451 / 614	16F/2R PowerDrive or CVXDrive	10,092	159 (216 or 428)	76 (91)
QUADTRAC 525 STEIGER 525	386 / 525	425 / 578	16F/2R PowerDrive or CVXDrive	10,092	159 (216 or 428)	76 (91) -
STEIGER 475	349 / 475	384 / 522	16F/2R PowerDrive or CVXDrive	10,092	159 (216 or 428)	-


¹⁾ ECE R120 corresponds to ISO 14396 and 97 / 68 / EC







caseih.com

 Free phone: 00 800 22 73 44 00



Subscribe now
for exclusive
offers & updates

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants.

TP01 / SM / 09.24 / Printed in Austria - Cod.No. 24C0007COMINB

CASE IH