MY25 TRAXTER PRO XU HD10 T ABS



Compass Green

Others

ENGINES HD10 Туре 82 hp / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled, catalytic converte Intelligent Throttle Control (iTC[™]) with Electronic Fuel Delivery System Fuel Injection (EFI) Transmission PRO-TORQ CVT with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P Drive Train Selectable Turf Mode / 2WD / 4WD with open front differential with ABS system Electronic Hill Descent Control Driving Assistance ECO™ / ECO™ Off / Work modes Speed Limiter Power Steering Dynamic Power Steering (DPS™) SUSPENSIONS Front Suspension Arched double A-arm / 11 in. (27.9 cm) suspension travel Front Shocks Twin tube gas charged shocks Rear Suspension Arched TTA with external sway bar / 11 in. (27.9 cm) suspension travel Rear Shocks Twin tube gas charged shocks **TIRES / WHEELS** Maxxis Coronado 2.0† 27 x 9/11 x 14 in. Front / Rear Tires Wheels 14 in. cast-aluminum BRAKES Front Dual 220 mm disc brakes with hydraulic twin-piston calipers Rear Dual 220 mm disc brakes with hydraulic

twin-piston calipers

Brake holding mechanism

PACKAGE HIGHLIGHTS

- Dynamic Power Steering (DPS[™])
- Full heater
- 4,500 lb (2,041 kg) winch with roller fairlead
- RF key DESS with Start / Stop button
- Evap system ready (CARB)
- Horn with turning signal lever
- Flashers and position lamps

DIMENSIONS / CAPACITIES

- Left and right sides EC approved mirrors
- Hook on front metal bumper
- Speed limiter: 40 60 Top speed (Km/h)
- ABS system

Cage	Profiled cage. ROPS approved
Estimated Dry Weight*	1,964 lb (891 kg)
LxWxH	154.1 x 64 x 78 in. (391.5 x 162.5 x 198.1 cm)
Wheelbase	115.5 in. (294 cm)
Ground Clearance	12.5 in. (32 cm)
Cargo Box Dimensions	72 x 54.5 x 10 in. (180,3 x 138.4 x 25.4 cm)
Cargo Box Capacity	1,200 lb (544 kg)
Power tilt bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	Total: 94 gal (356 L)
Towing Capacity	2,500 lb (1,134 kg)
Payload Capacity	1,700 lb (771 kg)
Fuel Capacity	10.6 gal (40 L)
Person Capacity	3
FEATURES	
Gauge	7.6 in. wide digital display with keypad
Battery	12-V (30 amp/h)
Magneto	650-W
Instrumentation	DC outlet (10-A)
Lighting	Front lighting output 140-W LED tail lights

modiamontation	Doodlot(10).
Lighting	Front lighting output 140-W LED tail lights
Winch	4,500 lb (2,041 kg) winch with roller fairlead
Seat	60/40 VERSA-PRO bench seat with passenger seats flipping up, underside hooks, reinforced seat skin adjustable driver seat
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper HMWPE full skid plate Front fender extension
Hitch Type	2 in. hitch receiver with rear hitch, tow ball and trailer connexion

WARRANTY & EXTENDED SERVICE

Factory warranty	2-year BRP limited warranty	
------------------	-----------------------------	--





REQUEST A QUOTE



©2024 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. ‡Visco-Lok is a trademark of GKN Viscodrive GmbH. †All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety: the operator and passengers hould wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.