

FARMALL 55-75 A

FARMALL 55-75 A

TRACTORS FROM
55 – 75 HP



CASE **II**

CASE **II**

EASE YOUR WORKLOAD

The Farmall 55-75 A

FARMALL 55-75 A

The Farmall A models redefine compactness, cost-effectiveness, and user-friendliness. With three models, 55, 65 and 75hp, Case IH offers rugged, reliable, and economical machines. Their straightforward operation, nimble maneuverability, and lightweight design make them versatile for various tasks, from light field duties to yard work and loader tasks. Additionally, their low maintenance requirements and efficient yet powerful engines ensure minimal running costs. Whatever your workload entails, the Farmall A series is up to the challenge.

PROVEN POWER

- Maximize fuel efficiency with the 2.9-litre FPT engine, no DEF/AdBlue needed
- Ensure constant power from 1,900-2,300 rpm
- Extend oil change intervals to 600 hours for reduced maintenance downtime

MAXIMUM VERSATILITY

- Two-speed rear PTO (540/540E)
- 3-point hitch with 3.0 t linkage capacity option
- 3 rear remotes and 2 mid-mount valves

SUPERIOR EASE OF USE

- 4WD limited slip front axle
- 40 kph maximum operating speed
- Enhanced versatility with a 20F/20R creeper option for speeds down to 100 meters/hr on 4WD models
- Enjoy clutchless forward/reverse operation with the optional 12F/12R powershuttle on 4WD models



EASY ACCESS AND OPTIMAL VISIBILITY


- Instruction seat and flat floor cab
- 4-post cab with high visibility panel and adjustable steering column
- Integral loader joystick option

IDEAL FOR LOADER WORK

- Factory-installed loader with mechanical self-leveling and 3rd function
- Tight turning radius of 4.7 m
- 12x12 transmission with powershuttle to speed up directional changes

MODEL	FARMALL 55A	FARMALL 65A	FARMALL 75A
ENGINE	FPT	FPT	FPT
Number of cylinders / Capacity (cm³)	3 / 2,930	3 / 2,930	3 / 2,930
Type / Emission level	Common Rail Diesel engine, turbocharged and intercooled / EURO Stage V		
Rated power ECE R120 ³ @ engine rpm (kW/hp(CV))	41 / 55 @ 2,300	48 / 65 @ 2,300	55 / 75 @ 2,300
Maximum torque ECE R120 ³ @ engine rpm (Nm @ rpm)	258 @ 1,400	291 @ 1,400	341 @ 1,400
Torque rise acc. OECD (%)	52	46	49
Fuel tank capacity (litres)	82	82	82
TRANSMISSION			
8 x 8 Synchroshift with mechanical shuttle, 30 kph	•	•	•
12 x 12 Synchroshift with mechanical shuttle and creeper, 40 kph	•	•	•
12 x 12 Synchroshift with Powershuttle, 40 kph	•	•	•
20 x 20 Synchroshift with Powershuttle and creeper, 40 kph	•	•	•
POWER TAKE OFF			
Engagement type	Mechanical lever / Servo assisted		
Speeds Standard (Option) (rpm)	540 (540/540E)		
Ground drive optional available for PTO (rpm)	540/540E		
FRONT PTO AND HITCH			
Front PTO 1,000 Speed @ 1,920 rpm	-	-	-
Front hitch max. lift capacity (kg)	-	-	-
FOUR WHEEL DRIVE AND STEERING (DRIVELINE)			
Type	electro-hydraulic		
Min. turning radius ² (m)	3.75 (2WD) / 4.71 (4WD)	3.75 (2WD) / 4.71 (4WD)	3.75 (2WD) / 4.71 (4WD)
HYDRAULIC SYSTEM			
Max. pump flow rate Total (Steering/Rear Hitch & External) (l/min)	47,7 (29 / 36,3)	47,7 (29 / 36,3)	47,7 (29 / 36,3)
MHC - Mechanical Hitch Control	•	•	•
EHC - Electronical Hitch Control	-	-	-
Max. lift capacity / OECD lift capacity through range @ 610 mm (kg)	2,700 / 3,000	2,700 / 3,000	2,700 / 3,000
Max. number of rear remote valves / mid mount valves	3 mechan. / 2 mechan.	3 mechan. / 2 mechan.	3 mechan. / 2 mechan.
WEIGHTS AND DIMENSIONS¹			
Approximate shipping weight (kg)	2,880	2,880	2,880
Permissible total weight standard 2WD / 4WD (kg)	4,500 / 4,800	4,500 / 4,800	4,500 / 4,800
Total height (mm)	2,495	2,495	2,495
Total length (mm)	3,856	3,856	3,856
Total width (across steps) (mm)	1,922	1,922	1,922
Wheel base 2WD / 4WD (mm)	2,085 / 2,123	2,085 / 2,123	2,085 / 2,123
STANDARD TYRES²			
Front	320/70 R20	12.4 R20	12.4 R20
Rear	420/70 R28	420/70 R28	420/70 R28

- Standard Equipment ◊ Optional Equipment - Not available
¹ With standard tyres ² Other tyres on request ³ ECE R120 correspond to ISO 14396 and 97 / 68 / EC

 Free phone: 00 800 22 73 44 00

   
 caseih.com

Safety never hurts! Always read the Operator's Manual before working with any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends **AKCELA** lubricants.